

NS-3A SERIES

Semi Auto Strapping Machine

NS-3AD

STANDARD MODEL



- Forward and reverse strap feeding units are separated and for easy adjustment.



NS-3AL

LOW-TABLED MODEL

NS-3ADM

MEDIUM-SIZED MODEL



MEDIUM-SIZED MODEL
STAINLESS STEEL FRAME

NS-3ADMS



FEATURES:

- Easy adjustment of tension on control panel by setting the electromagnetic clutch system.
- Low power consumption on 2 steps tensioning and 0.2V seal blade design allows for a very low Watt/Ampere level.
- Easy changing of straps design to give a convenient replacement on different strap thickness.
- Dual tensioning keeps proper bending power on the strap to avoid defected strapping. First step of the cycle reverse the strap around the package and second step to apply positive mechanical tension that can be adjusted by a twist of a dial on the panel.
- Designed for durable and convenient uses and provided with compact storage, this model highlights a precision performance and trouble-free maintenance with patent.
- Silent operation design of this model can suspend after each strapping cycle, advanced strap feed kept down the noise unlike the startup sounds of the old systems.
- Advanced devices of safety and convenience such as smoke vent, pneumatic tabletop, one-touch tension roller cleaning, tabletop folded edges and CE approved safety switches.

MODEL	NS-3AD	NS-3AL (Low-tabled Model)	NS-3ADM (Medium-Sized Model)	NS-3ADMS (Stainless Steel Frame)
Strap Cycle Speed	2 sec./ cycle	2 sec./ cycle	2 sec./ cycle	2 sec./ cycle
Tension Strength	4~80kg	4~80kg	1.5~60kg	1.5~60kg
Table Height	760mm	400mm	750mm	760mm
Strap Width	5~15.5mm	5~15.5mm	5~15.5mm	5~15.5mm
Sealing Method	Heat Sealed	Heat Sealed	Heat Sealed	Heat Sealed
Electric Consumption	200W	200W	200W	200W
Power Supply	110/220V 50/60Hz single phase	110/220V 50/60Hz single phase	110/220V 50/60Hz single phase	110/220V 50/60Hz single phase
Dimension	940W x 610D x 760H mm	1530W x 610D x 400H mm	860W x 570D x 750H mm	860W x 570D x 750H mm
Net Weight	110kg	86kg	86kg	86kg

LEG AND BODY K/D ASSEMBLY

Easy K/D assembly unit makes for compact shipping and delivery



Compact Model with Digital Display
Tension Adjustment

NS-3ADFD

- Smoke collector with active carbon filter (Optional)



NS-3ADF COMPACT MODEL

- Easy Leg and Body K/D assembly units make for compact shipment and delivery.

- Pneumatic Table Top Hinge



MODEL	NS-3ADFD (with Digital Display)	NS-3ADF (Compact Model)
Strap Cycle Speed	2 sec./ cycle	2 sec./ cycle
Tension Strength	1.5~60kg	1.5~60kg
Table Height	760mm	760mm
Strap Width	5~15.5mm	5~15.5mm
Sealing Method	Heat Sealed	Heat Sealed
Electric Consumption	200W	200W
Power Supply	110/220V/240V single phase	110/220V 50/60Hz single phase
Dimension	760W x 560D x 760H mm	760W x 560D x 760H mm
Net Weight	83kg	83kg

CHALI® Strapping Systems

NS-3A SERIES

SEMI-AUTO STRAPPING MACHINE

The technical design and system are provided by Kioritz Corporation Japan

- Heavy - duty Robust Design
- Silent Low Noise Operation
- Low Power Consumption
- Control Panel Tension Adjustment
- Added Safety Devices

